

# Node.js - NPM

Node Package Manager (NPM) provides two main functionalities –

Online repositories for node.js packages/modules which are searchable on [search.npmjs.org](https://search.npmjs.org)

Command line utility to install Node.js packages, do version management and dependency management of Node.js packages.

NPM comes bundled with Node.js installables after v0.6.3 version. To verify the same, open console and type the following command and see the result –

```
$ npm --version
2.7.1
```

If you are running an old version of NPM then it is quite easy to update it to the latest version. Just use the following command from root –

```
$ sudo npm install npm -g
/usr/bin/npm -> /usr/lib/node_modules/npm/bin/npm-cli.js
npm@2.7.1 /usr/lib/node_modules/npm
```

## Installing Modules using NPM

There is a simple syntax to install any Node.js module –

```
$ npm install <Module Name>
```

For example, following is the command to install a famous Node.js web framework module called express –

```
$ npm install express
```

Now you can use this module in your js file as following –

```
var express = require('express');
```

## Global vs Local Installation

By default, NPM installs any dependency in the local mode. Here local mode refers to the package installation in `node_modules` directory lying in the folder where Node application is present. Locally deployed packages are accessible via `require()` method. For example, when we installed `express` module, it created `node_modules` directory in the current directory where it installed the `express` module.

```
$ ls -l
total 0
drwxr-xr-x 3 root root 20 Mar 17 02:23 node_modules
```

Alternatively, you can use **`npm ls`** command to list down all the locally installed modules.

Globally installed packages/dependencies are stored in system directory. Such dependencies can be used in CLI (Command Line Interface) function of any `node.js` but cannot be imported using `require()` in Node application directly. Now let's try installing the `express` module using global installation.

```
$ npm install express -g
```

This will produce a similar result but the module will be installed globally. Here, the first line shows the module version and the location where it is getting installed.

```
express@4.12.2 /usr/lib/node_modules/express
├─ merge-descriptors@1.0.0
├─ utils-merge@1.0.0
├─ cookie-signature@1.0.6
├─ methods@1.1.1
├─ fresh@0.2.4
├─ cookie@0.1.2
├─ escape-html@1.0.1
├─ range-parser@1.0.2
├─ content-type@1.0.1
├─ finalhandler@0.3.3
├─ vary@1.0.0
├─ parseurl@1.3.0
├─ content-disposition@0.5.0
├─ path-to-regexp@0.1.3
├─ depd@1.0.0
├─ qs@2.3.3
├─ on-finished@2.2.0 (ee-first@1.1.0)
├─ etag@1.5.1 (crc@3.2.1)
├─ debug@2.1.3 (ms@0.7.0)
├─ proxy-addr@1.0.7 (forwarded@0.1.0, ipaddr.js@0.1.9)
├─ send@0.12.1 (destroy@1.0.3, ms@0.7.0, mime@1.3.4)
├─ serve-static@1.9.2 (send@0.12.2)
├─ accepts@1.2.5 (negotiator@0.5.1, mime-types@2.0.10)
└─ type-is@1.6.1 (media-typer@0.3.0, mime-types@2.0.10)
```

You can use the following command to check all the modules installed globally –

```
$ npm ls -g
```

# Using package.json

package.json is present in the root directory of any Node application/module and is used to define the properties of a package. Let's open package.json of express package present in **node\_modules/express/**

```
{
  "name": "express",
  "description": "Fast, unopinionated, minimalist web framework",
  "version": "4.11.2",
  "author": {
    "name": "TJ Holowaychuk",
    "email": "tj@vision-media.ca"
  },
  "contributors": [{
    "name": "Aaron Heckmann",
    "email": "aaron.heckmann+github@gmail.com"
  },
  {
    "name": "Ciaran Jessup",
    "email": "ciaranj@gmail.com"
  },
  {
    "name": "Douglas Christopher Wilson",
    "email": "doug@somethingdoug.com"
  },
  {
    "name": "Guillermo Rauch",
    "email": "rauchg@gmail.com"
  },
  {
    "name": "Jonathan Ong",
    "email": "me@jongleberry.com"
  },
  {
    "name": "Roman Shtylman",
    "email": "shtylman+expressjs@gmail.com"
  },
  },
}
```

```
{
  "name": "Young Jae Sim",
  "email": "hanul@hanul.me"
} ],

"license": "MIT", "repository": {
  "type": "git",
  "url": "https://github.com/strongloop/express"
},

"homepage": "https://expressjs.com/", "keywords": [
  "express",
  "framework",
  "sinatra",
  "web",
  "rest",
  "restful",
  "router",
  "app",
  "api"
],

"dependencies": {
  "accepts": "~1.2.3",
  "content-disposition": "0.5.0",
  "cookie-signature": "1.0.5",
  "debug": "~2.1.1",
  "depd": "~1.0.0",
  "escape-html": "1.0.1",
  "etag": "~1.5.1",
  "finalhandler": "0.3.3",
  "fresh": "0.2.4",
  "media-typer": "0.3.0",
  "methods": "~1.1.1",
  "on-finished": "~2.2.0",
  "parseurl": "~1.3.0",
  "path-to-regexp": "0.1.3",
  "proxy-addr": "~1.0.6",
  "qs": "2.3.3",
  "range-parser": "~1.0.2",
  "send": "0.11.1",
  "serve-static": "~1.8.1",
  "type-is": "~1.5.6",
  "vary": "~1.0.0",
  "cookie": "0.1.2",
  "merge-descriptors": "0.0.2",
  "utils-merge": "1.0.0"
},

"devDependencies": {
  "after": "0.8.1",
  "ejs": "2.1.4",
```

```
"istanbul": "0.3.5",
"marked": "0.3.3",
"mocha": "~2.1.0",
"should": "~4.6.2",
"supertest": "~0.15.0",
"hjs": "~0.0.6",
"body-parser": "~1.11.0",
"connect-redis": "~2.2.0",
"cookie-parser": "~1.3.3",
"express-session": "~1.10.2",
"jade": "~1.9.1",
"method-override": "~2.3.1",
"morgan": "~1.5.1",
"multiparty": "~4.1.1",
"vhost": "~3.0.0"
},

"engines": {
  "node": ">= 0.10.0"
},

"files": [
  "LICENSE",
  "History.md",
  "Readme.md",
  "index.js",
  "lib/"
],

"scripts": {
  "test": "mocha --require test/support/env
    --reporter spec --bail --check-leaks test/ test/acceptance/",
  "test-cov": "istanbul cover node_modules/mocha/bin/_mocha
    -- --require test/support/env --reporter dot --check-leaks test/ test/acceptance/",
  "test-tap": "mocha --require test/support/env
    --reporter tap --check-leaks test/ test/acceptance/",
  "test-travis": "istanbul cover node_modules/mocha/bin/_mocha
    --report lcovonly -- --require test/support/env
    --reporter spec --check-leaks test/ test/acceptance/"
},

"gitHead": "63ab25579bda70b4927a179b580a9c580b6c7ada",
"bugs": {
  "url": "https://github.com/strongloop/express/issues"
},

"_id": "express@4.11.2",
"_shasum": "8df3d5a9ac848585f00a0777601823faecd3b148",
"_from": "express@*",
"_npmVersion": "1.4.28",
"_npmUser": {
  "name": "dougwilson",
```

```
    "email": "doug@somethingdoug.com"
  },
  "maintainers": [{
    "name": "tjholowaychuk",
    "email": "tj@vision-media.ca"
  },
  {
    "name": "jongleberry",
    "email": "jonathanrichardong@gmail.com"
  },
  {
    "name": "shtylman",
    "email": "shtylman@gmail.com"
  },
  {
    "name": "dougwilson",
    "email": "doug@somethingdoug.com"
  },
  {
    "name": "aredridel",
    "email": "aredridel@nbtsc.org"
  },
  {
    "name": "strongloop",
    "email": "callback@strongloop.com"
  },
  {
    "name": "rfeng",
    "email": "enjoyjava@gmail.com"
  }
  ],
  "dist": {
    "shasum": "8df3d5a9ac848585f00a0777601823faecd3b148",
    "tarball": "https://registry.npmjs.org/express/-/express-4.11.2.tgz"
  },
  "directories": {},
  "_resolved": "https://registry.npmjs.org/express/-/express-4.11.2.tgz",
  "readme": "ERROR: No README data found!"
}
```

# Attributes of Package.json

**name** – name of the package  
**version** – version of the package  
**description** – description of the package  
**homepage** – homepage of the package  
**author** – author of the package  
**contributors** – name of the contributors to the package  
**dependencies** – list of dependencies. NPM automatically installs all the dependencies mentioned here in the `node_modules` folder of the package.  
**repository** – repository type and URL of the package  
**main** – entry point of the package  
**keywords** – keywords

## Uninstalling a Module

Use the following command to uninstall a Node.js module.

```
$ npm uninstall express
```

Once NPM uninstalls the package, you can verify it by looking at the content of `/node_modules/` directory or type the following command –

```
$ npm ls
```

## Updating a Module

Update `package.json` and change the version of the dependency to be updated and run the following command.

```
$ npm update express
```

## Search a Module

Search a package name using NPM.

```
$ npm search express
```

# Create a Module

Creating a module requires package.json to be generated. Let's generate package.json using NPM, which will generate the basic skeleton of the package.json.

```
$ npm init
This utility will walk you through creating a package.json file.
It only covers the most common items, and tries to guess sane defaults.

See 'npm help json' for definitive documentation on these fields
and exactly what they do.

Use 'npm install <pkg> --save' afterwards to install a package and
save it as a dependency in the package.json file.

Press ^C at any time to quit.
name: (webmaster)
```

You will need to provide all the required information about your module. You can take help from the above-mentioned package.json file to understand the meanings of various information demanded. Once package.json is generated, use the following command to register yourself with NPM repository site using a valid email address.

```
$ npm adduser
Username: mcmohd
Password:
Email: (this IS public) mcmohd@gmail.com
```

It is time now to publish your module –

```
$ npm publish
```

If everything is fine with your module, then it will be published in the repository and will be accessible to install using NPM like any other Node.js module.

---

Revision #1

Created 16 December 2022 09:18:45 by Admin

Updated 16 December 2022 09:19:35 by Admin